

DUSH RESINA 1610



SIZES

5 Kg

COLORS

Crystal

AREA OF USE

Marble & Granite

COMPONENT A

PHYSICAL STATE		Liquid
DENSITY at 20°C		1.1 g/cm ³
COLOUR		Transparent

DESCRIPTION:

DUSH RESINA 1610 is a high-performance crystal clear resin designed for filling and repairing marble, granite, and natural stone. As an advanced version, it is made from unsaturated polyester with orthophthalic modified resin and standard glycol, pre-accelerated with hardener. Known for its chemical and mechanical resistance, brightness, and stability after hardening, Dush Resina 1610 is ideal for stuccoing and gluing marble slabs, stones, agglomerates, and travertine.

Product Application Photo:



INSTRUCTIONS TO USE:

1. Clean the surface of stone of all dust and dirt and make it completely dry.
2. Take required quantity of 'resin' and add '1% to 3% catalyst' depending on usage conditions.
3. Mix the two components well.
4. Apply the mixture on the joints and holes to get a perfect surface.

FEATURES AND BENEFITS:

1. **Crystal Clear Clarity:** Offers superior transparency, making it perfect for seamless repairs and fillings in marble, granite, and other natural stones.
2. **Enhanced Durability:** Exhibits excellent chemical and mechanical resistance, ensuring long-lasting stability and brightness after hardening.
3. **Versatile Application:** Suitable for stuccoing and gluing a variety of stones, including marble slabs, agglomerates, and travertine, providing a versatile solution for stone maintenance.
4. **Customizable Consistency:** Can be diluted with monomer styrene to improve spreading and impregnation, allowing for precise application tailored to specific needs.
5. **Pigment Compatibility:** Allows the addition of coloring pastes or pigments, enabling custom color matching for repairs without significantly affecting the resin's performance.

PRECAUTIONS AND NOTES:

1. Wear Hand Gloves.
2. Keep Out of Reach of Children.
3. Keep the application area enough ventilated.
4. Keep the product closed after usage and away from sunlight.
5. Always test the product before use.

HANDLING & SHELF-LIFE:

Keep the tins closed and stored in a cool and ventilated environment at a temperature of 28–35 °C, away from the source of heat. Best Before 12 months.

SAFETY RULES:

Keep the application area enough ventilated. Keep the tins closed after usage and away from sunlight. Please read carefully the safety data sheet before usage. Always test the product before use.

TECHNICAL INFORMATION :

COMPONENT A

PHYSICAL STATE		Liquid
DENSITY at 20°C		1.1 g/cm ³
COLOUR		Transparent

CHARACTERISTICS OF PRODUCT

Aspect of Product	Liquid Clear
Viscosity at 23°C	400-500mPa·s

DUSH 

Toll Free No: 18008910133, E-MAIL: india@dushproducts.com

Website: dushproducts.com

Italy 

Via Roma, 2 Lancenigo di Villorba-31020, Treviso(TV) ITALY

DISCLAIMER:

Before using any Dush products, test on a small, inconspicuous area to ensure compatibility and understand the application process. Results may vary based on application methods, surface conditions, and climate factors such as temperature and humidity. While Dush aims to provide high-quality products, we cannot guarantee specific results due to these variables. By using Dush products, you acknowledge and accept that Dush shall not be held liable for any damage or unsatisfactory results arising from their use or misuse.