

EPO MASTICS

Epoxy-Based Translucent Stone Repair & Bonding Compound

Technical Properties

Appearance: Translucent, Ultra-fine paste

Base Chemistry: Epoxy Resin

Mixing Ratio: 100 : 50

Pot Life: 30–40 minutes @ 25°C

Initial Dry Time: 45–60 minutes

Full Cure: 24 hours

Shrinkage: Nil

Flexibility: High

Water Resistance: Excellent

Weather Resistance: Excellent

Salt Rise Resistance: Yes

Traffic Resistance: High

Yellowing: No



Description

EPO MASTICS is a high-performance, two-component epoxy-based mastic developed for permanent bonding, filling, finishing, and repairing marble, granite, and natural stone. Its ultra-fine translucent formulation ensures excellent shade matching and becomes an integral part of the stone after curing.

Application Method

1. Clean loose dust (slight dirt acceptable)
2. Mix **Part A & Part B** as per ratio
3. Apply using spatula / knife
4. Allow initial setting
5. Proceed with grinding & polishing

Packing

1.5kg Set (Part A 1kg+ Part B 500gms.)

Shelf Life

12 months (sealed, cool & dry storage)

DISCLAIMER:

Before using any Dush products, test on a small, inconspicuous area to ensure compatibility and understand the application process. Results may vary based on application methods, surface conditions, and climate factors such as temperature and humidity. While Dush aims to provide high-quality products, we cannot guarantee specific results due to these variables. By using Dush products, you acknowledge and accept that Dush shall not be held liable for any damage or unsatisfactory results arising from their use or misuse.