

DUSH SPN 1650 2+1



SIZES

3 kg set

COLORS

Transparent

AREA OF USE

COMPONENT A

PHYSICAL STATE

Liquid

DENSITY at 20°C

1.14 g/cm

COLOUR

Clear

COMPONENT B

Liquid

100 g/cm3

Clear

DESCRIPTION:

DUSH SPN1650 is a premier filling adhesive and sealant crafted from a dual-component epoxy system, ideal for beige and light shades of grey marble. Serving as a protective barrier against UV rays while remaining transparent, this product is favored by professionals for filling air cracks and pinholes. It safeguards the stone from staining and preserves the surface polish for long-lasting beauty.

Product Application Photo:



INSTRUCTIONS TO USE:

1. Clean the marble surface by removing all dust and dirt.
2. Mix the two components Epoxy and Hardener in 100(Resin):50(Hardner) ratio.
3. Apply the mixture on the cleaned surface with putty blade thoroughly to fill cracks and pin holes.
4. Allow it to dry for 24 hours and continue with next steps.

FEATURES AND BENEFITS:

1. **UV Protection:** Acts as a transparent shield against harmful UV rays, preserving the natural beauty of marble surfaces.
2. **Professional-Grade:** Trusted by professionals for filling air cracks and pinholes, ensuring seamless repairs and enhancements.
3. **Stain Prevention:** Protects marble from staining, maintaining its pristine appearance over time.
4. **Surface Polish Preservation:** Ensures the longevity of surface polish, keeping marble surfaces looking glossy and refined.
5. **Versatile Application:** Suitable for various light-colored marble shades, offering a reliable solution for a range of marble restoration and maintenance needs.

PRECAUTIONS AND NOTES:

1. Wear Hand Gloves.
2. Keep Out of Reach of Children.
3. Keep the application area enough ventilated.
4. Keep the product closed after usage and away from sunlight.
5. Always test the product before use.

HANDLING & SHELF-LIFE:

Keep the tins closed and stored in a cool and ventilated environment at a temperature of 28-35 °C, away from the source of heat. Best Before 12 months.

SAFETY RULES:

Keep the application area enough ventilated. Keep the tins closed after usage and away from sunlight. Please read carefully the safety data sheet before usage. Always test the product before use.

TECHNICAL INFORMATION :

	COMPONENT A	COMPONENT B
PHYSICAL STATE	Liquid	Liquid
DENSITY at 20°C	1.14 g/cm ³	1.00g/cm ³
COLOUR	Clear	Clear
VISCOSITY	900-1500 mPa.s (25°C)	200 mPa.s (25

CHARACTERISTICS OF PRODUCT	
Aspect of Product	Clear Liquid
Vapour Density	N.A
PHR	100:25

DUSH 

Toll Free No: **18008910133**, E-MAIL: india@dushproducts.com

Website: dushproducts.com

Italy 

Via Roma, 2 Lancenigo di Villorba-31020, Treviso(TV) ITALY

DISCLAMIER:

Before using any Dush products, test on a small, inconspicuous area to ensure compatibility and understand the application process. Results may vary based on application methods, surface conditions, and climate factors such as temperature and humidity. While Dush aims to provide high-quality products, we cannot guarantee specific results due to these variables. By using Dush products, you acknowledge and accept that Dush shall not be held liable for any damage or unsatisfactory results arising from their use or misuse.